

## Durable Label Materials

Removable labels for temporary labeling or protection of glass, plastics, metal and more

## **Durable Label Materials**

## A selection of adhesives and facestocks stay stuck as you need, but remove cleanly when the job is done.

- Temporary protection of surfaces from dirt, debris and damage during handling
- No adhesive residue and film splinters upon removal
- Choice of polyester, vinyl, polypropylene and paper facestocks

## 3M<sup>™</sup> Removable Label Material

Product	Typical Performance Characteristics	Construction		Roll Width	Print	Specs
		Caliper Mils	Facestock Adhesive Type Liner	Minimum Mini-Master (shown in red)	Method	
3M <sup>™</sup> Removable Label Material FM01860N	Removable for many uses including graphic protection.	2.0 0.8 1.0	Clear Polyester <b>R3500</b> Clear Polyester Liner	54" 1668' Min.	Flexo, TTa	RoHS
3M <sup>™</sup> Removable Label Material FP0862	Clear conformable label offers long term adhesion with clean removability. Excellent alternative to static cling.	2.0 0.8 3.2	Clear Polypropylene TC2S <b>R3500</b> 50# SC	54" 1668' Min. <mark>6</mark> "	Flexo	RoHS
3M <sup>™</sup> Removable Label Material FP016902	Good conformability. Good removability from a variety of surfaces. Excellent alternative to static cling.	2.3 0.8 3.2	White Polypropylene TC2S <b>R3500</b> 50# SC	54" 1668' Min. <mark>6</mark> "	Flexo	RoHS
3M <sup>™</sup> Removable Label Material 7065	Ultra removable from smooth surfaces. Topcoated. Excellent alternative to static cling.	3.2 0.8 6.8	Soft White Vinyl <b>R3500</b> 90# Polycoated Kraft	Sheet - 20" x 27" Master - 54" x 750'	Screen	RoHS
3M <sup>™</sup> Removable Label Material 7142	Good thermal transfer printable facestock. Can be removed cleanly or repositioned on most substrates.	3.5 0.4 2.5	55# White Coated Paper <b>1000</b> 40# Kraft Glassine	48" 1668' Min. <mark>6</mark> "	Flexo, TT	UL RoHS
3M <sup>™</sup> Removable Label Material 7600	Top-coated, high bond, but offers clean removability on most surfaces for up to one year. Excellent for plasticizer resistance.	3.5 1.0 2.5	Soft White Gloss Vinyl TC <b>500</b> 43# Densified Kraft	54" 1668' Min. <mark>6</mark> "	Flexo	RoHS

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted.



**Converter Markets** 

Industrial Adhesives and Tapes Division 3M Center Building 225-3S-06 St. Paul, MN 55144 Tel: 800-362-3550 3M.com/converter

3M and 3M Science Applied to Life are trademarks of 3M Company. © 3M 2017. All rights reserved. 70-0713-4576-6